

# POSHTECH

立式綜合加工機



久洋機械股份有限公司

## NVM1010-5A



### Standard :

- \* Spindle Speed 15000rpm, Power 18.5Kw
- \* XYZ Linear Way: German Rexroth.
- \* Splash coolant Sheet metal
- \* Spindle coolant
- \* Spindle Air below
- \* Chip flow on Base
- \* Chip screw on Base
- \* Chip conveyor
- \* Lubrication
- \* Alarm & work lamp
- \* Spindle coolant System
- \* XYZ Special Ballscrew

### Option :

- \* CTS : 20 Bar 600L
- \* XYZ Axis Linear Scale
- \* AC Axis Encoder
- \* Auto Tool Length Measurement
- \* Auto Workpiece Measurement
- \* ArmType Magazine

**Jeou Yang Machinery Co.,LTD**

No197,Min-Sheng St,Tan-Tzu,Taichung,Taiwan

TEL : + 886-4-2537-0971

FAX : + 886-4-2537-0984

E-mail : [poshtech@ms36.hinet.net](mailto:poshtech@ms36.hinet.net)

Model		NVM1010-5A
<b>Table</b>		
Table Size (X/Y)mm		1350×1100
Max workpiece mm		1000x1000x700
Cylinder workpiece mm		Dia 630,High700
Table Load kg		1000
<b>Travel</b>		
X Travel (X) mm		1200
Y Travel (Y) mm		1100
Z Travel (Z) mm		650
A Axis		90 , -120
C Axis Table mm		Dia 550mm
Spindle nose to Table mm		200-850
Column Distance mm		1250
<b>Spindle</b>		
Spindle		Built-in HSK63A
Spindle Speed ( STD ) rpm		15000
Spindle Lube		Grease
Spindle Coolant		Oil 6000 Kcal
<b>Feed</b>		
Rapid Rate M/min		36/36/36
Min Feed mm		0.001
<b>ATC</b>		
Tool Type		HSK63A
Tool capacity pcs		60 Arm Type
Max Tool Diameter mm		80
Max Tool Length mm		300
Max Tool Weight kg		7
Tool Change Time		2.5 sec
<b>Servo Motor</b>		
Spindle motor Kw		18.5
X Servo motor Kw		5.0
Y Servo motor Kw		5.0
Z Servo motor Kw		5.0+B
<b>Machine Weight &amp; Dimension</b>		
Machine Dimension mm		4200×3200x4000
Machine Weight kg		9500

\* Specification is subject to be changed without notice.