

POSHTECH

立式綜合加工機



久洋機械股份有限公司

POSHTECH

NV1512



Standard Accessories :

- * Massive iron construction
- * 8000rpm Spindle Speed
- * Direct-coupled servo motors
- * Full splash safety guard
- * Air cooling system
- * Spindle air blast (Taper)
- * Spindle air blower
- * Auto lubrication system
- * Cycle end alarm light
- * Halogen work lamp
- * Leveling blots and pads
- * Toolkit box
- * Operation & Maintenance Manual

Optional Accessories :

- * 18000/DD Spindle speed
- * Oil cooler for spindle
- * CNC Rotary Table
- * Auto Tool Length Measurement

E-mail : JEOU YANG MACHINERY CO.,LTD.

NO.197,MIN-SHENG ST.,TAN-TZU

TAICHUNG,TAIWAN ,ROC.

TEL : + 886-4-2537-0971

FAX : + 886-4-2537-0984

E-mail : poshtech@ms36.hinet.net

POSHTECH

Model	NV1512	
Table		
Table size (X/Y) mm	2000×1100	
T-slot (size * number)	1500x1100x650	
Max. Table loading	kg	2000
Travel		
Longitudinal travel (X) mm	1500	
Cross travel (Y) mm	1200	
Headstock travel (Z) mm	650	
Spindle nose to table surface	200-850	
Spindle Center to Column	1250	
Spindle		
Spindle taper	BT40	
Spindle speed (standard) rpm	8,000	
Spindle Cooling	air	
Feed		
Rapid travel	M/min	30/30/30
Min. input increment	mm	0.001
ATC		
Tool holder	BT40	
Tool storage capacity	pcs	40 std /60 opt
Max. Tool diameter	mm	80
Max. Tool length	mm	300
Max. Tool weight	kg	7
Tool change time	2.5 sec	
Motor		
Spindle motor	Kw	11/15
X servo motor	Kw	A22
Y servo motor	Kw	A22
Z servo motor	Kw	A22B
Machine weight and space		
Floor space	mm	4800×3000x3700
Net weight	kg	9500

* Specification is subject to be changed without notice.